





Introducing the AccurioPrint C4065 – the incredibly versatile digital printer that connects you with success. The outstanding image and colour quality, media versatility, and fast 65 colour ppm or 80 black & white ppm output make this press a high-value, yet cost-effective solution for print professionals.

# ACCURIOPRINT C4065 SPECIFICATIONS

# **RETHINK OPTIONS**

# SYSTEM SPECIFICATIONS

| Resolution        | 3,600 (equivalent) x 2,400 dpi x 8 bit |  |
|-------------------|--|--|
| Paper weight      | 62 – 360 g/m²                          |  |
| Paper sizes       | 330.2 x 487.7 mm                       |  |
|                   | 330.2 x 862 mm (max.duplex)            |  |
|                   | 330.2 x 1300 mm (max. simplex)         |  |
| Paper input       | Max.: 7,380 sheets                     |  |
| Dimension (WxDxH) | 31.49" x 35.55" x 42.36"               |  |
| Unit weight       | 696.66 lb.                             |  |

# **PRODUCTIVITY**

| AccurioPrint C4065         |        |  |
|----------------------------|--------|--|
| 8.5 x 11 – max. per minute | 65 ppm |  |
| 11 x 17 - max. per minute  | 36 ppm |  |

# KONICA MINOLTA IMAGE CONTROLLER IC-607

| Architecture              | Internal  |
|---------------------------|---|
| OS                        | Linux   |
| CPU                       | Intel Pentium C4400   |
| Clock speed               | 3.3 GHz   |
| RAM std                   | 16 GB   |
| HDD                       | 2 TB (2 x 1TB)  |
| Page-description language | Adobe PostScript 3; PDF v1.7; TIFF (v6); PPML v2.2                  |
| Applicable OS             | Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14 |

### FIERY IMAGE CONTROLLER IC-419

| Architecture              | Internal   |
|---------------------------|--|
| OS                        | Linux  |
| CPU                       | Intel® Pentium® Processor G4400  |
| Clock speed               | 3.3 GHz  |
| RAM std                   | 8 GB   |
| HDD                       | 500 GB   |
| Page-description language | Adobe® PostScript® Levels 1, 2, 3, APPE 5, Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders) |
| Applicable OS             | Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14  |
|                           |  |

#### **OPTIONS**

| KM Image Controller                  | IC-607    |
|--------------------------------------|-----------|
| EFI internal Controller              | IC-419    |
| Paper Feeding Unit                   | PF-602m   |
| Dehumidifier heater                  | HT-504    |
| Paper feeding unit                   | PF-707m   |
| Dehumidifier heater                  | HT-506    |
| PFU connection Kit                   | FA-502    |
| Large capacity feeding unit          | LU-202m   |
| Dehumidifier heater f. LU            | HT-503    |
| Envelop printing guidef. LU          | MK-746    |
| Large capacity feeding unit (banner) | LU-202XLm |
| Multi bypass feeding                 | MB-508    |
| Banner Paper Feeder kit              | MK-760    |
| Multi bypass tray                    | MB-509    |
| Intelligent Media Sensor             | IM-101    |
| Output Tray                          | OT-511    |
| Stapling Unit                        | FS-532m   |
| Saddle Stitcher Kit                  | SD-510    |
| Punch Kit                            | PK-525    |
| Post Inserter Kit                    | PI-502    |
| Output Tray Unit                     | OT-512    |
| Long Sheet Kit (Output)              | MK-761    |
|                                      |           |

# DF-713 — DUAL SCAN DOCUMENT FEEDER (OPTION)

| Tray Capacity            | 300 sheets (80 gsm)   |                        |                                    |                                  |  |
|--------------------------|---|------------------------|------------------------------------|----------------------------------|--|
| Original Weight Duplex   | 50 – 210 gsm  |                        |                                    |                                  |  |
| Detectable Document Size | Min: 3.94" x 5.51" (100 x 140 mm)<br>Max: 11.69" x 17" (297 x 431.8 mm) |                        |                                    |                                  |  |
| Scan Speed by Resolution | 200 dpi   | Colour:<br>Monochrome: | Simplex 140 ipm<br>Simplex 140 ipm | Duplex 280 ipm<br>Duplex 280 ipm |  |
|                          | 300 dpi   | Colour:<br>Monochrome: | Simplex 120 ipm<br>Simplex 120 ipm | Duplex 240 ipm<br>Duplex 240 ipm |  |
|                          | 400 dpi   | Colour:<br>Monochrome: | Simplex 100 ipm<br>Simplex 100 ipm | Duplex 200 ipm<br>Duplex 200 ipm |  |
| Copy Speed               | 600 dpi   | Colour:<br>Monochrome: | Simplex 75 ipm<br>Simplex 80 ipm   | Duplex 150 ipm<br>Duplex 160 ipm |  |

- -All specifications refer to A4-size paper of 80 gsm quality.
- -The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- -The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- -Some of the product illustrations contain optional accessories
- -Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- -Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- -All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.





KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Suite 100, Mississauga, Ontario L4W 0E1

www.konicaminolta.ca

